



DM SILENT SERIES DIESEL GENERATOR SETS

Silent generator sets are suitable for areas with strict requirements on noise and other special requirements as telecom, bank, large building, airport etc. Silent generator sets are scientifically designed by using advanced technologies on acoustics and breath subject, adopt brand-name engine and generator and high quality of AVR, fine performances, high reliability, graceful in shape for outside cover, easy to dismantle, compact structure. Our products meet the standards ISO8528 and Gb2820.



ATS



DONGMING

GENERATOR SETS

TECHNICAL DATA

10~250

Type	GFS10	GFS12	GFS15	GFS20	GFS24	GFS30	GFS50	GFS75	GFS90	GFS120	GFS150	GFS200	GFS250	
Rated output (kW)	10	12	15	20	24	30	50	75	90	120	150	200	250	
Rated current (A)	18.1	21.7	27.1	36.1	43.3	54.1	90.2	135.3	162.4	216.5	270.6	360.5	451.1	
Disel Engine	Type	295AD	2100AD	395AD	495AD-13	495AZD-13	4135D	6135D	6135AD	6135AZD	12V135D	12V135AD	12V135AZD	
	12h power 12 (kW)	13.8	15.3	20.6	26.5(36)	35.3(48)	58.82(80)	88.2(102)	110.3(150)	154.4(210)	176.5(240)	236.8(315)	236.8(315)	
	Fuel consumption (g/kWh)	258.4	258.4	254.2	265.2(195)	233.7(172)	233.7(172)	238(175)	238(175)	238(175)	238(175)	238(175)	238(175)	
	Starting type	Electric starting (DC 12/24V)												
Generator	Rated power (kW)	10	12	15	20	24	30	50	75	90	120	150	200	250
	Excitation mode	Brush or brush less												
Net weight (kg)	800	850	980	1480	1580	1950	2500	3000	3180	3900	4900	5200	5830	

300~800

Type	DM S300	DM S350	DM S400	DM S500	DM S600	DM S800	
Rated output (kW/kVA)	300/375	350/450	400/500	500/625	600/750	800/1000	
Rated current (A)	541	656	721	902	1082	1443	
Disel Engine	Type	KTA19G2	KTA19G3	KTA19G4	KTA38G	KTA38G3	KTA38G5
	Fuel consumption (g/kWh)	83	97	107	142	170	201
	Starting type	Electric starting (DC 12/24V)					
Generator	Rated power (kW/kVA)	300/375	350/450	400/500	500/625	600/750	800/1000
	Excitation mode	Brush or brush less					
Net weight (kg)	4800	5050	5600	7500	9950	10760	