

THREE-PHASE Double-Polarity ASYNCHRONOUS MOTORS

ALUMINUM HOUSING

MSD



MSD Series Three-Phase Double Speed Asynchronous Motors are extending products of MS Series motors. There are two polarities of 2/4; 4/8 in single winding, and 2/6; 2/8; 4/6; 6/8 in double winding.



Technical data (at 400V/50Hz)

Model	Power kW		Speed rpm		Eff η %	Power Factor COS ϕ		Current A		Rated Torque Nm		Tst/Tn Times		Ist/In Times		Tmax/Tn Times		
	2P	4P	2P	4P		2P	4P	2P	4P	2P	4P	2P	4P	2P	4P	2P	4P	
MSD631-2/4	0.15	0.11	2680	1340	54	50	0.68	0.63	0.59	0.50	0.54	0.79	2	2	3.5	3.5	2	2
MSD632-2/4	0.22	0.15	2690	1340	58	53	0.72	0.65	0.76	0.63	0.78	1.07	2	2	3.5	3.5	2	2
MSD711-2/4	0.3	0.22	2750	1350	60	55	0.8	0.73	0.90	0.79	1.04	1.56	1.7	1.7	3.5	3.5	1.9	1.9
MSD712-2/4	0.45	0.3	2790	1380	63	58	0.8	0.73	1.29	1.02	1.54	2.08	2	2	4	4	2	2
MSD801-2/4	0.55	0.45	2800	1380	65	64	0.84	0.75	1.45	1.35	1.88	3.11	2	2	4.5	4.5	2.1	2.1
MSD802-2/4	0.75	0.6	2800	1400	67	68	0.86	0.77	1.88	1.65	2.56	4.09	1.8	1.8	4.5	4.5	2	2
MSD90S-2/4	1.25	0.95	2820	1400	72	68	0.86	0.82	2.91	2.46	4.23	6.48	2	2	5	5	2	2
MSD90L-2/4	1.7	1.32	2830	1400	73	70	0.86	0.83	3.91	3.28	5.74	9.00	2	2	5	5	2	2
MSD100L1-2/4	2.4	1.84	2830	1410	73	76	0.86	0.83	5.52	4.21	8.10	12.46	2	2	5.5	5	2	2
MSD100L2-2/4	3.3	2.6	2840	1420	74	78	0.86	0.85	7.48	5.66	11.10	17.19	2	1.9	5.5	5	2	1.9
MSD112M-2/4	4.5	4	2860	1430	77	79	0.85	0.86	9.92	8.50	15.03	26.71	2	1.8	5.5	5	2.2	2
MSD132S-2/4	6	5	2860	1440	79	82	0.84	0.86	13.05	10.23	20.03	33.16	2	1.5	5.5	5.5	2.2	1.9
MSD132M-2/4	8	6.6	2870	1440	82	84	0.84	0.86	16.76	13.09	26.62	43.77	2	2	6	6	2.2	2.2
MSD160M-2/4	11	9	2920	1450	84	84	0.85	0.82	22.23	18.86	35.98	59.28	1.8	1.8	7	6	2	2
MSD160L-2/4	15	12	2920	1450	86	84	0.87	0.83	28.94	24.84	49.06	79.03	2	2	7	7	2.2	2.2

Technical data (at 400V/50Hz)

Model	Power kW		Speed rpm		Eff η %	Power Factor COS ϕ		Current A		Rated Torque Nm		Tst/Tn Times		Ist/In Times		Tmax/Tn Times		
	4P	8P	4P	8P		4P	8P	4P	8P	4P	8P	4P	8P	4P	8P	4P	8P	
MSD801-4/8	0.25	0.15	1380	680	58	40	0.77	0.60	0.81	0.90	1.73	2.11	2	2	4.5	3	2	2
MSD802-4/8	0.45	0.25	1390	685	68	48	0.80	0.60	1.19	1.25	3.09	3.49	1.8	2	4.5	3	2	2
MSD90S-4/8	0.55	0.3	1400	690	68	50	0.83	0.61	1.41	1.42	3.75	4.15	1.8	2	4.5	3.5	2	2
MSD90L-4/8	0.8	0.45	1400	690	68	53	0.83	0.63	2.05	1.95	5.46	6.23	1.8	1.6	4	3	1.9	1.8
MSD100L1-4/8	1.25	0.6	1400	700	69	54	0.82	0.56	3.19	2.86	8.53	8.16	1.8	2	5	3.5	2	2
MSD100L2-4/8	1.76	0.88	1400	700	71	58	0.84	0.56	4.26	3.91	12.00	12.00	1.8	2	5.5	4	2	2
MSD112M-4/8	2.2	1.5	1420	700	75	64	0.82	0.61	5.16	5.54	14.80	20.46	2	2	6	4	2	2
MSD132S-4/8	3.3	2.2	1430	705	78	70	0.84	0.64	7.27	7.09	22.04	29.8	2	2	6	5	2	2
MSD132M-4/8	4.5	3	1430	705	82	77	0.85	0.65	9.32	8.65	30.05	40.64	2	2	6	5	2	2
MSD160M1-4/8	5.5	4	1440	710	82	77	0.81	0.69	11.95	10.87	36.48	53.80	2.1	1.7	7.6	4.6	2.3	2.2
MSD160M2-4/8	7.5	5	1440	710	82	79	0.89	0.78	14.83	11.71	49.74	67.25	1.7	1.6	6.6	4.5	2.3	2.1
MSD160L-4/8	10	7	1450	715	84	82	0.90	0.78	19.09	15.80	65.86	93.50	1.8	1.9	5.5	5	2.3	2.1

MSD Three-Phase Dual-Polarity Asynchronous Motors

www.dongmingmotor.com
business@dongmingmotor.com

Technical data (at 400V/50Hz)

Model	Power kW		Speed rpm		Eff η %	Power Factor COS ϕ		Current A		Rated Torque Nm		Tst/Tn Times		Ist/In Times		Tmax/Tn Times		
	4P	6P	4P	6P		4P	6P	4P	6P	4P	6P	4P	6P	4P	6P	4P	6P	
MSD801-4/6	0.3	0.22	1400	910	60	55	0.74	0.69	0.98	0.84	2.05	2.31	2	1.8	4.5	4	2	2
MSD802-4/6	0.45	0.3	1410	920	63	58	0.75	0.7	1.37	1.07	3.05	3.11	2	1.8	4.5	4	2	2
MSD90S-4/6	0.66	0.45	1410	920	66	61	0.76	0.65	1.9	1.64	4.47	4.67	1.7	1.7	5	4.5	2	2
MSD90L-4/6	0.88	0.6	1420	930	70	64	0.77	0.67	2.36	2.02	5.92	6.16	1.7	1.7	5	4.5	2	2
MSD100L1-4/6	1.32	0.88	1420	940	72	67	0.85	0.75	3.11	2.3	8.88	8.94	1.8	1.8	6	5	2	2
MSD100L2-4/6	1.76	1.2	1430	950	74	70	0.85	0.75	4.04	3.3	11.75	12.06	1.8	1.8	6	5	2	2
MSD112M-4/6	2.2	1.5	1430	950	76	70	0.8	0.70	5.22	4.42	14.69	15	2	1.8	6	5	2.2	2.2
MSD132S-4/6	3.3	2.2	1440	960	82	78	0.81	0.72	7.17	5.65	21.9	21.9	2	2	7	6	2.2	2.2
MSD132M-4/6	4.5	3	1450	970	83	80	0.82	0.74	9.54	7.31	29.6	29.5	2	2	7	6	2.3	2.3
MSD160M-4/6	6.6	4.5	1460	970	84	81	0.84	0.78	13.5	10.3	43.2	44.3	1.8	1.8	7	6	2.3	2.3
MSD160L-4/6	8.8	6	1460	970	84	81	0.85	0.79	17.8	13.5	57.6	59.1	1.8	1.8	7	6	2.3	2.3

Technical data (at 400V/50Hz)

Model	Power kW		Speed rpm		Eff η %	Power Factor COS ϕ		Current A		Rated Torque Nm		Tst/Tn Times		Ist/In Times		Tmax/Tn Times		
	6P	8P	6P	8P		6P	8P	6P	8P	6P	8P	6P	8P	6P	8P	6P	8P	
MSD801-6/8	0.18	0.11	900	680	50	42	0.69	0.65	0.75	0.58	1.91	1.54	1.5	1.5	3.5	3	1.5	1.5
MSD802-6/8	0.25	0.18	920	700	54	46	0.7	0.66	0.95	0.86	2.60	2.46	1.7	1.5	3.5	3	1.5	1.7
MSD90S-6/8	0.37	0.25	930	680	58	50	0.72	0.68	1.28	1.06	3.80	3.51	1.5	1.4	4	3	1.8	1.7
MSD90L-6/8	0.55	0.37	940	685	63	54	0.73	0.69	1.73	1.43	5.59	5.16	1.5	1.4	4	3	1.8	1.7
MSD100L1-6/8	0.75	0.55	950	700	69	63	0.74	0.74	2.12	1.70	7.54	7.50	1.5	1.4	5	4	2	1.8
MSD100L2-6/8	1.03	0.75	955	705	71	65	0.76	0.76	2.76	2.19	10.30	10.16	1.5	1.4	5	4	2	1.8
MSD112M-6/8	1.25	0.95	960	710	72	64	0.71	0.71	3.53	3.02	12.43	12.78	1.5	1.5	5	4	2	1.8
MSD132S-6/8	2.2	1.5	970	720	76	70	0.71	0.7	5.88	4.42	21.66	19.90	1.6	1.4	6	5.5	2.3	2
MSD132M-6/8	3	1.85	970	720	78	74	0.71	0.7	7.82	5.01	29.54	24.37	1.6	1.4	6	5.5	2.3	2
MSD160M1-6/8	3.7	2.6	970	720	78	75	0.74	0.71	9.25	7.05	36.43	34.49	1.8	1.5	6	5.5	2.5	1.9
MSD160M2-6/8	4.5	3.3	970	720	79	76	0.78	0.72	10.54	8.70	44.30	43.77	1.8	1.7	6	5.5	2.5	2
MSD160L-4/6	6	4.5	973	720	80	77	0.79	0.73	13.70	11.55	59.89	59.69	1.8	1.7	6	5.5	2.5	2

Technical data (at 400V/50Hz)

Model	Power kW		Speed rpm		Eff η %	Power Factor COS ϕ		Current A		Rated Torque Nm		Tst/Tn Times		Ist/In Times		Tmax/Tn Times		
	2P	8P	2P	8P		2P	8P	2P	8P	2P	8P	2P	8P	2P	8P	2P	8P	
MSD801-2/8	0.37	0.08	2760	660	65	33	0.76	0.48	1.08	0.73	1.28	1.16	1.7	2	3.5	2.5	1.9	2.1
MSD802-2/8	0.55	0.11	2780	670	67	35	0.78	0.50	1.52	0.91	1.89	1.57	1.7	2	4	3	1.9	2.2
MSD90S-2/8	0.75	0.18	2800	670	67	43	0.79	0.52	2.05	1.16	2.56	2.57	1.8	2	4	3	2	2.3
MSD90L-2/8	1.1	0.3	2810	680	67	45	0.8	0.54	2.96	1.78	3.74	4.21	1.8	2	4	3.5	2	2.3
MSD100L1-2/8	1.5	0.37	2820	700	67	50	0.84	0.56	3.85	1.91	5.08	5.05	1.7	2.1	5	3.5	2	2.6
MSD100L2-2/8	2.2	0.55	2820	710	68	51	0.85	0.58	5.49	2.68	7.45	7.40	1.8	2.2	5	3.5	2	2.6
MSD112M1-2/8	2.6	0.75	2840	710	71	58	0.86	0.6	6.15	3.11	8.74	10.09	1.8	1.8	5.5	4	1.9	1.9
MSD112M2-2/8	3	0.9	2850	710	75	63	0.86	0.58	6.71	3.56	10.05	12.1	1.7	2	6.5	4.5	1.9	2.2
MSD132S-2/8	3.7	1.1	2890	710	81	65	0.83	0.57	7.94	4.29	12.22	14.80	1.7	1.7	7	5	1.9	1.9
MSD132M-2/8	5.5	1.5	2900	720	82	66	0.85	0.57	11.39	5.75	18.11	19.90	1.8	1.8	7	5	1.9	1.9
MSD160M-2/8	7.5	2.2	2900	720	80	73	0.87	0.58	15.55	7.50	24.70	29.18	2.3					